Aura Series

Flat Flood Lights



Product Offers:

Model #	Power Consumption	Light Output	Replaces
M-FD-F-70	70W	9,500Lm	250W PSMH
M-FD-F-105	105W	12,000Lm	320W PSMH
M-FD-F-150	150W	18,000Lm	400W PSMH
M-FD-F-250	250W	33,000Lm	750W PSMH





Applications:

- Building facades, displays, landscaping, security, parking areas, walkways, and other work areas
- Ideal for replacing 250W to 750W pulse start metal halide (PSMH) flood light fixtures with 70W to 250W LED fixtures

Features:

- Maximum light output for general flood light and security lighting
- Daylight white light color (5,000K)
- Rated for damp and wet locations
- One piece die-cast aluminum housing with integrated cooling fins and durable powder coat finish in Dark Bronze with UV resistant polycarbonate optical lens UL Listed and DLC Qualified
- IP66 rated LED light engine eliminates the need for a glass lens for maximum light output
- 50,000 hour rated Life Span
- Voltage: 120V or 120V 277V
- 70 CRI
- PF ≥ 0.9
- Mounting options trunnion mount, 2 3/8" OD slipfitter mount, and wall mount
- Warranty: 5 year limited
- Options: surge protection and photocell



Eos Illumination 7111 Dixie Highway Ste 333 Clarkston, MI 48348 Phone 248-558-3050 EosIllumination.com **Eos Illumination - North** 817 E State St. Ste 102 Cheboygan, MI 49721