

Helios Series Linear High Bay Lights



Applications:

- Designed to replace conventional HID and fluorescent high bav fixtures
- \checkmark Suitable for mounting heights ranging from 15'-45' in warehouses, factories, loading docks, parking structures, distribution centers, convention centers, gymnasiums, commercial, retail, and other institutional applications.

Features:

- \checkmark Maximum light output for safety, security and general purpose lighting in high ceiling applications
- \checkmark Daylight white light color (5,000K)
- \checkmark 0-10V dimmable standard
- ✓ Die-cast aluminum housing in white
- \checkmark Prismatic Diffuser, Medium lens and Aisle lens available
- \checkmark Vastly superior color rendition index compared to HPS
- \checkmark UL Listed for damp location
- \checkmark UL Listed and DLC Qualified
- \checkmark 50,000 hour rated Life Span
- \checkmark Voltage: 120V - 277V
- \checkmark $PF \ge 0.9$
- \checkmark Installation: conduit or pendant chain
- \checkmark Warranty: 5 year limited
- \checkmark Options: motion sensor, emergency backup, wire guard, pendant hanger, lenses

Model #	Power Consumption	Light Output	Efficacy	Size	CRI
M-HBL-80	80W	11,500Lm	144	2'x2'	80
M-HBL-105	105W	13,600Lm	129	2'x2'	80
M-HBL-160	160W	22,200Lm	139	2'x2'	80
M-HBL-200	200W	25,800Lm	129	2'x4'	82
M-HBL-320	320W	43,800Lm	137	2'x4'	82

2'x4' 320W medium lens





Eos Illumination 7111 Dixie Highway Ste 333 Clarkston, MI 48348 Phone 248-558-3050 EosIllumination.com

Product Offers: